

## Classic 18

When you need a little more cooling than the Classic 10, but still want maximum portability, the MovinCool Classic 18 portable air conditioner fits the bill. With standard 230V power, this unit is instantly ready to provide cool air anywhere. It is designed to work in the hottest environments such as production lines, outdoor events, manufacturing processes, injection molding, metal forming and much more. By cooling only the area that needs it, the Classic 18 saves you money while protecting people and equipment and speeding up processes.

Self-contained and portable, the Classic 18 requires little or no installation - simply roll it in, plug it in and turn it on.

- Handles temperatures up to 105°F, provides cooling in the hottest environments
- 18,000 Btu/h cooling capacity to handle any hot spot
- Half the cost of central air conditioning, cooling for as little as 20 cents per hour
- Rugged design. Proven durability since 1982



# MOVINCOOL®

THE #1 SPOT COOLING SOLUTION

800.264.9573

www.movincool.com

DENSO SALES CALIFORNIA, Inc. 3900 Via Oro Ave. Long Beach, CA 90810



## Technical Specs

## Classic 18\*

Electronic Features	Control Panel Thermostat Control	Digital Electronic
Cooling Capacity	Rating Conditions: 95°F at 60% RH	18,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 208/230V 1.9 kW 8.8 amps 15 amps 6 - 15 198 – 250
Fans	Motor Output - high/low	0.35 kW
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 530 CFM 0.48 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 1180 CFM 0.25 IWG
Compressor	Type Output	Hermetic Rotary 1.1 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	19 x 26 x 41 in
Net Weight/Shipping Weight		164/205 lb
Power Cord	Gauge/Length	14 AWG (3-core)/6 ft
Condensate Tank Capacity		5 gal
Operating Conditions	Min. – Max. (@ 50% RH)	70° - 105°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	50 ft 60 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	63 dB(A) 67 dB(A)

All specifications subject to change without notice.

\* Specification information shown with 230V

© 2010 DENSO SALES CALIFORNIA, INC. MovinCool, SpotCool and Office Pro are registered trademarks of DENSO Corporation.

360-0110-C18